



Hydraulic Breaker


Easily smash through concrete, even on an incline, with the hardest hitting breakers in their respective impact energy classes. Vibration and shock are controlled by shock absorbing polymers, minimizing machine wear and sound while improving operator comfort level. The Hydraulic Breaker makes quick work out of a tough job.



FEWER MOVING PARTS WITH A 2 YEAR WARRANTY PROVIDE ULTIMATE RELIABILITY

COMES STANDARD WITH MOIL AND CHISEL TOOLS TO HANDLE ANY DEMOLITION PROJECT

MAXIMUM VISIBILITY FOR PRECISE TOOL PLACEMENT





Take a Picture of This QR Code With Your Smart Phone to See it in Action



SKID STEER

FEATURES & BENEFITS

- Nitrogen charged increases efficiency and overall breaking force over competitors
- Bolt-on mounting plate allows for skid steer or mini excavator fitment
- Built in dampener's lower vibration and noise
- Easy to maintain with replaceable bushings
- Easy access grease points for in field maintenance

SPECIFICATIONS / OPTIONS

Model	750		1150	
Part Number	901983	902016	901984	902017
Shipping Weight	1,030 lbs.	760 lbs.	1,250 lbs.	980 lbs.
Energy Class	750 ft-lb	750 ft-lb	1150 ft-lb	1150 ft-lb
Minimum Operating Machine	7,500 lbs.	7,500 lbs.	10,000 lbs.	10,000 lbs.
Minimum Operating Pressure	2,000 psi	2,000 psi	2,200 psi	2,200 psi
Oil Flow Range	10-20 GPM	10-20 GPM	15-25 GPM	15-25 GPM
Impact Rate	500-900 BPM	500-900 BPM	400-800 BPM	400-800 BPM
Tool Diameter	2.7"	2.7"	3.0"	3.0"
Mount	Skid Steer	Various	Skid Steer	Various

Options

Factory Installed Couplers

* For more specification details please see our website www.erskineattachments.com